


**RF/IR/UV ATTENUATION LAMINATE**



**PRODUCT DETAILS**

PRODUCT CLASS	SIGNAL ATTENUATION
RF (30MHz-6+GHz)	>33 dB
IR TRANSMISSION	<3% (800-1500nm)
UV TRANSMISSION	<1%
VLT (400-780nm)	>65%
SHGC / ShadingCO	.47 / .55
LAMINATE THICKNESS	.437" (7/16")

**TESTING PROTOCOLS**

RF & IR Are Typical Values As Tested By The United States Department of Defense

**DESCRIPTION**

The LTI-SD1000/0716-AG product provides the HIGHEST levels of RF and IR attenuation, meets and exceeds the requirements of various US Government organizations' specifications for optically clear RF/IR/UV attenuating film/optical coatings, especially with respect to IR, and is listed by DoD as an RF/IR Attenuation film tested to be "beneficial" as Alternative Shielding including TEMPEST Countermeasures.

**GLAZING INFORMATION**

The LTI Group strongly suggests the use of a suitable structural security framing with an appropriate protection rating.

A minimum framing engagement of one (1) inch is recommended, (Larger lites may require deeper engagements.)

It is imperative to the life and durability of certain composite types that compatible sealant or gasket material is used on both sides of the laminate. An appropriate sealant solution can be specified by LTI if required.

The LTI Group produces the finest glass and composite laminates in the world, proper care during installation will ensure years of superior performance.

**LTI-SD1000/0716-AG SPECIFICATION**

Annealed Glass x2 plies  
Clear custom adhesive interlayer x2 plies  
SD1000 Signal Attenuation Film x1 ply  
5 Individual layers make up the LTI-SD1000/0716-AG composite product

Additional Optional Product Features:  
3M™ VHB™ Acrylic Foam Tape For Non-Mechanical Adhesion  
Self Adhering Chrome Finish Corner Edge Frame

**STANDARDS**

ASTM C 1036-01 For Flat glass  
ASTM C 1172-96 For Laminated Architectural Flat Glass  
ASTM C1349 For Laminate Quality  
ANSI Z97.1.1984 (R1975) For Safety Glazing Materials Used In Buildings

**MANUFACTURER INFORMATION**

**LTI SMART GLASS, INC.**  
LENOX, MASS. +1.413.637.5001  
**LAMINATED TECHNOLOGIES, INC.**  
MELBOURNE, FL +1.321.751.1130

**WARRANTY**

Limited Warranty- LTI warranties the LTI-SD1000/0716-AG laminate system against plastic delamination for a 3 year period from date of shipment see additional warranty details online at [www.LTISG.com](http://www.LTISG.com).